



TruVis DOS

Product Data Sheet		
PRODUCT/CLASS	Diocetyl sebacate; Diester of sebacic acid	
MANUFACTURING LOCATION	Brownsville, Tennessee	
AVAILABILITY	US. Additional Country Availability information on request.	
MARKET	Industrial, Transportation, Metalworking	
USES/CLAIMS	Base Oil; Lubricant	
APPLICATIONS	Grease, Engine, MWF-neat	
PROPERTY	TYPICAL VALUE	TEST METHOD
VISCOSITY @ 40°C	11.7 cSt	ASTM D445-09
VISCOSITY @ 100°C	3.23 cSt	ASTM D445-09
VISCOSITY INDEX	140	
POUR POINT	- 80 °C	ASTM D5950-02
FLASH POINT, COC	230 °C	ASTM D92-05A
NOACK VOLATILITY, % LOSS		ASTM D5800A
SPECIFIC GRAVITY @ 20°C	0.915	ASTM D4052-09
COLOR, PT CO	50	ASTM D1209-05
PURITY, ESTER CONTENT	99.0	ASTM D3465
ACID VALUE	0.05 mgKOH/g	ASTM D974-08
HYDROLYTIC STABILITY	+ 0.01 mgKOH/g Δ	ASTM D2619
MOISTURE CONTENT	500 ppm	ASTM E1064-08
SEDIMENT, INSOLUBLE CONTAMINATION	3.5 mg/L	

Customer Service:
1-800-554-9887
Fax: 401-724-6250



Teknor Apex Company
505 Central Avenue
Pawtucket, Rhode Island 02861
www.teknorapex.com/truvis